

Edilkamin S.p.A. 20020 Lainate (MI), via P. Mascagni 7 Tel. +39 02 937621 Fax +39 02 93762 400/300 mail@edilkamin.com www.edilkamin.com Capitale € 4.100.000 int. vers. Sede legale: 20123 Milano, via Vincenzo Monti 47 Reg. Imp. di Milano 00192220192 REA n° 878888 Cod. Fiscale e Partita IVA 00192220192

Declaration of performance

According to Regulation (EU) No. 305/2011

N. EK182

1. Unique identification code of the product-type

BLOKK 70

2. Intended uses of the product in accordance with the applicable harmonized technical specification

Insert or open fireplace by solid fuel (wood logs) , without hot water production

3. Name or trade mark of the manufacturer (Article 11-5)

EDILKAMIN S.p.A.

Via Mascagni, 7 – 20020 Lainate (MI) Italy tel. +39 02 937621 – mail@edilkamin.com

4. Name and address of the agent (Article 12-2)

5. Assessment and verification system for constancy of performance (Annex 5)

System 3

6a. Harmonized technical specification Laboratory notified EN 13229:2001/AI:2003/A2:2004/AC:2006/AC:2007

ACTECO Sri - NB1880

7. Declared performance

Declared perio	inidite			
Essential characteristics		Performance		
Reaction to fire		A1		
Distance to combustible materials		▲ C Rear = 200		
ř	(minimum distance in mm)	R _ Sides = 300		
		Front =		t = 800
		C K I -F	Ceiling	g = NPD
		³ ♦ FI	Floo	r = NPD
	Risk of burning fuel falling out	Pass		
	Emission of combustion products	Rated fuel load		Reduced fuel load
	CO (ref. at 13% O ₂)	893 mg/Nm ³ - 0,07 %		- mg/Nm³ %
	NOx (ref. at 13% O₂)	111 mg/Nm ³		- mg/Nm³
	OGC (ref. at 13% O ₂)	37 mg/Nm ³		- mg/Nm³
	Particulate matter (ref. at 13% O ₂)	8 mg/Nm ³		- mg/Nm ³
Surface temperature		Pass		
Electrical safety		NPD		
Cleanability		Pass		
Maximum operating pressure		- bar		
Mechanica	al resistance (to carry a chimneyflue)	Pass		
	Thermal output	Rated fuel lo	oad	Reduced fuel load
Nominal heat output		14,3 kW	/	- kW
Nominal space heating output		14,3 kW	•	- kW
Nominal boiler output (to water)		- kW	1	- kW
Energy efficiency		81,4 %		- %
	Flue gas temperature	T[252°C]	}	T[- °C]

8. Test report number (based on System 3)

1880-CPR-076-19

The performance of the product identified in point 1 is in conformity with the declared performance in points 6a and 7. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Lainate, 30/09/2020

Signed for and on behalf of Edilkamin S.p.A. by:

Legal Representative

Luca Borsatti